

INDUSTRIAL COMPONENT DATA

412521 IME CONTACTOR 16A NA+NC 230V

Brand: IME | Manufacturer Part Number: 412521



Manufacturer	IME
MPN / Reference	412521
Catalog number	412521
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-1BE9E18F9E
Generated	2026-07-29

Product Overview

CONTACTOR 16A NA+NC 230V

Contactor with coil 230V~ - 2P - 250V~ - 16A - NC+NA - 1 module

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

Contactor 16A open contact+closed contact 230V. Contactors with coil 230V~ Bipolar 250V~ - I max.: 16A - Contact type: NC + NA - Number of modules: 1. CX³ contactors - without manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 250-250 V
Rated Operating Current 16 A
Control voltage rating (Min-Max) 195-253 V
Operating voltage type AC
Voltage Type (Excitation Voltage) AC
Number of contacts normally opened 1
Number of Normally Closed Contacts 1
Maximum incandescent lamp load 2000 W
Maximum fluorescent lamp load 1300 VA
Maximum fluorescent lamp load (duo circuit) 1400 VA
Maximum fluorescent lamp load (parallel-compensated) 600 VA
Slider for manual operation Yes
Width in number of modular spaces 1

Installation Depth 44 mm
Additional equipment possible Yes
Protection Class (IP) IP2X
Width 17.8 mm
Height 94.9 mm
Depth 67.3 mm
Impact resistance IK04
Operating Temperature (Min-Max) -25-60 °C
Storage Temperature (Min-Max) -40-70 °C
Frequency (Min-Max) 50-60 Hz
Display of markings on the connection terminals Yes
Colour Grey
RAL number 7035
Halogen-free Yes
Terminal Capacity (Min-Max) 0.75-6 mm²
Connection type Cable
Label Space/Print Area Yes
Type of mounting DIN Lane
ETIM for 412521 Modular devices for distribution board/surface mounting (EC001653)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
1300 VA
Rated operation current (EF007679)
16 A
Degree of prote...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412521 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.