

INDUSTRIAL COMPONENT DATA

412533 IME CONTACTOR 25A 2NA+2NC 230V

Brand: IME | Manufacturer Part Number: 412533



Manufacturer	IME
MPN / Reference	412533
Catalog number	412533
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-8C695D5F1C
Generated	2026-07-29

Product Overview

CONTACTOR 25A 2NA+2NC 230V

Contactor with coil 230V~ - 4P - 400V~ - 25A - 2NC+ 2NA - 2 modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

Contactor 25A 2NA+2NC 230V. Contactors with coil 230V~ Tetrapolar 400V~ - I max.: 25A - Contact type: 2 NC + 2 NA - Number of modules: 2. CX³ contactors - without manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 250-250 V

Rated Operating Current 25 A

Control voltage rating (Min-Max) 195-253 V

Operating voltage type AC

Voltage Type (Excitation Voltage) AC

Number of contacts normally opened 2

Number of Normally Closed Contacts 2

Maximum incandescent lamp load 3000 W

Maximum fluorescent lamp load 2100 VA

Maximum fluorescent lamp load (duo circuit) 2200 VA

Maximum fluorescent lamp load (parallel-compensated) 1000 VA

Slider for manual operation Yes

Width in number of modular spaces 2

Installation Depth 44 mm
Additional equipment possible Yes
Protection Class (IP) IP2X
Width 35.6 mm
Height 94.9 mm
Depth 67.3 mm
ETIM for 412533 Modular devices for distribution board/surface mounting (EC001653)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
2100 VA
Rated operation current (EF007679)
25 A
Degree of protection (IP) (EF005474)
IP2X
Width in number of modular spacings (EF002950)
2
Max. incandescent lamp load (EF004952)
3000 W
Additional equipment possible (EF008148)
Yes
Max. load fluorescent lamp (parallel compensated) (EF004973)
1000 VA
Max. load fluorescent lamp (Duo circuit) (EF004972)
2200 VA
Voltage type (excitation voltage) (EF005293)
AC
Number of con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412533 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.