

## INDUSTRIAL COMPONENT DATA

## 412544 IME \*CONTACTOR 25A 2NA 230V

Brand: IME | Manufacturer Part Number: 412544



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | IME                                           |
| MPN / Reference | 412544                                        |
| Catalog number  | 412544                                        |
| Category        | Installation contactor for distribution board |
| Minimum order   | 2 Pcs                                         |
| Document ID     | EO-7091A36C70                                 |
| Generated       | 2026-07-27                                    |

## Product Overview

\*CONTACTOR 25A 2NA 230V

Contactor with coil 230V~ - 2P - 250V~ - 25A - 2 NA - 1 module

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |     |
|--------------|-----|
| Catalog path | IME |
|--------------|-----|

## Additional Product Information

Contactor 25A 2NA 230V. Contactors with coil 230V~ - Forced running contactors without automatic return or stop to ensure the test function and repair Bipolar 250V~ - Max I: 25A - Contact type: 2 NA - Number of modules: 1. CX<sup>3</sup> contactors - with manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 250-250 V  
Rated Operating Current 25 A  
Control voltage rating (Min-Max) 195-253 V  
Operating voltage type AC  
Voltage Type (Excitation Voltage) AC  
Number of contacts normally opened 2  
Number of Normally Closed Contacts 0  
Maximum incandescent lamp load 3000 W  
Maximum fluorescent lamp load 2100 VA  
Maximum fluorescent lamp load (duo circuit) 2200 VA  
Maximum fluorescent lamp load (parallel-compensated) 1000 VA  
Slider for manual operation Yes

Width in number of modular spaces 1  
Installation Depth 44 mm  
Additional equipment possible Yes  
Protection Class (IP) IP2X  
Width 17.8 mm  
Height 94.9 mm  
Depth 72.6 mm  
Impact resistance IK04  
Operating Temperature (Min-Max) -25-60 °C  
Storage Temperature (Min-Max) -40-70 °C  
Frequency (Min-Max) 50-60 Hz  
Display of markings on the connection terminals Yes  
Colour Grey  
RAL number 7035  
Halogen-free Yes  
Terminal Capacity (Min-Max) 0.75-6 mm<sup>2</sup>  
Connection type Cable  
Label Space/Print Area Yes  
Type of mounting DIN Lane  
ETIM for 412544 Modular devices for distribution board/surface mounting (EC001653)  
Feature Name  
Feature Value  
Max. load fluorescent lamp (EF0...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412544 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.