

INDUSTRIAL COMPONENT DATA

412545 IME CONTACTOR 40A 2NA 230V

Brand: IME | Manufacturer Part Number: 412545



Manufacturer	IME
MPN / Reference	412545
Catalog number	412545
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-737D55EF77
Generated	2026-07-29

Product Overview

CONTACTOR 40A 2NA 230V

Contactor with coil 230V~ - 2P - 250V~ - 40A - 2 NA - 2 modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

40A 2NA 230V contactor. Contactors with 230V~ coil - Forced running contactors without automatic return or stop to ensure the test and repair function Bipolar 250V~ - Max I: 40A - Contact type: 2 NA - Number of modules: 2. CX³ contactors - with manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 250-250 V

Rated Operating Current 40 A

Control voltage rating (Min-Max) 195-253 V

Operating voltage type AC

Voltage Type (Excitation Voltage) AC

Number of contacts normally opened 2

Number of Normally Closed Contacts 0

Maximum incandescent lamp load 5000 W

Maximum fluorescent lamp load 3100 VA

Maximum fluorescent lamp load (duo circuit) 3400 VA

Maximum fluorescent lamp load (parallel-compensated) 1400 VA

Slider for manual operation Yes

Width in number of modular spaces 2

Installation Depth 44 mm

Additional equipment possible Yes

Protection Class (IP) IP2X

Width 68 mm

Height 94 mm

Depth 35.6 mm

ETIM for 412545 Modular devices for distribution board/surface mounting (EC001653)

Feature Name

Feature Value

Max. load fluorescent lamp (EF004971)

3100 VA

Rated operation current (EF007679)

40 A

Degree of protection (IP) (EF005474)

IP2X

Width in number of modular spacings (EF002950)

2

Max. incandescent lamp load (EF004952)

5000 W

Additional equipment possible (EF008148)

Yes

Max. load fluorescent lamp (parallel compensated) (EF004973)

1400 VA

Max. load fluorescent lamp (Duo circuit) (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412545 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.