

INDUSTRIAL COMPONENT DATA

412548 IME CONTACTOR 63A 2NC 230V

Brand: IME | Manufacturer Part Number: 412548



Manufacturer	IME
MPN / Reference	412548
Catalog number	412548
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-AF8B28D9DD
Generated	2026-07-29

Product Overview

CONTACTOR 63A 2NC 230V

Contactor with coil 230V~ - 2P - 250V~ - 63A - 2 NC - 2 modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

Contactor 63A 2NC 230V. Contactors with coil 230V~ - Forced running contactors without automatic return or stop to ensure the test and repair function Bipolar 250V~ - Max I: 63A - Contact type: 2 NC - Number of modules: 2. CX³ contactors - with manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 250-250 V
Rated Operating Current 63 A
Control voltage rating (Min-Max) 195-253 V
Operating voltage type AC
Voltage Type (Excitation Voltage) AC
Number of contacts normally opened 0
Number of Normally Closed Contacts 2
Maximum incandescent lamp load 8000 W
Maximum fluorescent lamp load 4700 VA
Maximum fluorescent lamp load (duo circuit) 5000 VA
Maximum fluorescent lamp load (parallel-compensated) 1700 VA
Slider for manual operation Yes

Width in number of modular spaces 2
Installation Depth 44 mm
Additional equipment possible Yes
Protection Class (IP) IP2X
Width 68 mm
Height 94 mm
Depth 35.6 mm
ETIM for 412548 Modular devices for distribution board/surface mounting (EC001653)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
4700 VA
Rated operation current (EF007679)
63 A
Degree of protection (IP) (EF005474)
IP2X
Width in number of modular spacings (EF002950)
2
Max. incandescent lamp load (EF004952)
8000 W
Additional equipment possible (EF008148)
Yes
Max. load fluorescent lamp (parallel compensated) (EF004973)
1700 VA
Max. load fluorescent lamp (Duo circuit) (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412548 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.