

## INDUSTRIAL COMPONENT DATA

## 412551 IME \*CONTACTOR 25A 4NA 230V

Brand: IME | Manufacturer Part Number: 412551



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | IME                                           |
| MPN / Reference | 412551                                        |
| Catalog number  | 412551                                        |
| Category        | Installation contactor for distribution board |
| Minimum order   | 1 Pcs                                         |
| Document ID     | EO-AB4D7DA48A                                 |
| Generated       | 2026-07-31                                    |

## Product Overview

\*CONTACTOR 25A 4NA 230V

Contactor with coil 230V~ - 4P - 250V~ - 25A - 4 NA - 2 modules

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |     |
|--------------|-----|
| Catalog path | IME |
|--------------|-----|

## Additional Product Information

25A 4NA 230V Contactor. Contactors with coil 230V~ - Forced running contactors without automatic return or stop to ensure the test function and repair Tetrapolar 400V~ - References 4 125 53/56/57 can be converted into group head with the connection module for contactor ref. 4 063 02 - Max I: 25A - Contact type: 4 NA - Number of modules: 2. CX<sup>3</sup> contactors - with manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 400-400 V  
Rated Operating Current 25 A  
Control voltage rating (Min-Max) 195-253 V  
Operating voltage type AC  
Voltage Type (Excitation Voltage) AC  
Number of contacts normally opened 4  
Number of Normally Closed Contacts 0  
Maximum incandescent lamp load 3000 W  
Maximum fluorescent lamp load 2100 VA  
Maximum fluorescent lamp load (duo circuit) 2200 VA  
Maximum fluorescent lamp load (parallel-compensated) 1000 VA

Slider for manual operation Yes  
Width in number of modular spaces 2  
Installation Depth 44 mm  
Additional equipment possible Yes  
Protection Class (IP) IP2X  
Width 35.6 mm  
Height 94.9 mm  
Depth 72.6 mm  
ETIM for 412551 Modular devices for distribution board/surface mounting (EC001653)  
Feature Name  
Feature Value  
Max. load fluorescent lamp (EF004971)  
2100 VA  
Rated operation current (EF007679)  
25 A  
Degree of protection (IP) (EF005474)  
IP2X  
Width in number of modular spacings (EF002950)  
2  
Max. incandescent lamp load (EF004952)  
3000 W  
Additional equipment possible (EF0...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412551 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.