

INDUSTRIAL COMPONENT DATA

412556 IME CX3 CONTACT 230V 4NA 63A MAN

Brand: IME | Manufacturer Part Number: 412556



Manufacturer	IME
MPN / Reference	412556
Catalog number	412556
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-08857F9314
Generated	2026-07-29

Product Overview

CX3 CONTACT 230V 4NA 63A MAN

Contactor with coil 230V~ - 4P - 250V~ - 63A - 4 NA - 3 modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

The CX³ range includes power or domestic contactors, as well as remote switches and indicator lights and switches with modular pushbuttons. All of these control devices are mounted on divider boxes and accept the passage of the power comb. Domestic contactors allow the management of the peak/off-peak rate of water heaters, for example, power contactors allow remote control of a load by means of a switch with or without a handle. Impulse switches are used to control the power supply to lighting circuits from different locations. Push buttons and push button switches are used to control electrical circuits. Rated Operating Voltage (Min-Max) 400-400 V

Rated Operating Current 63 A

Control voltage rating (Min-Max) 195-253 V

Operating voltage type AC

Voltage Type (Excitation Voltage) AC

Number of contacts normally opened 4

Number of Normally Closed Contacts 0

Maximum incandescent lamp load 8000 W

Maximum fluorescent lamp load 4700 VA

Maximum fluorescent lamp load (duo circuit) 5000 VA

Maximum fluorescent lamp load (parallel-compensated) 1700 VA
Slider for manual operation Yes
Width in number of modular spaces 3
Installation Depth 44 mm
Additional equipment possible Yes
Protection Class (IP) IP2X
Width 68 mm
Height 94 mm
Depth 53.4 mm
ETIM for 412556 Modular devices for distribution board/surface mounting (EC001653)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
4700 VA
Rated operation current (EF007679)
63 A
Degree of protection (IP) (EF005474)
IP2X
Width in numbe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412556 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.