

INDUSTRIAL COMPONENT DATA

412557 IME CX3 CT 230V 4NC 63A HANDLE

Brand: IME | Manufacturer Part Number: 412557



Manufacturer	IME
MPN / Reference	412557
Catalog number	412557
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-D6AC7E69EC
Generated	2026-08-01

Product Overview

CX3 CT 230V 4NC 63A HANDLE

Contactor with coil 230V~ - 4P - 250V~ - 63A - 4 NC - 3 modules

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

CX3CT 230V 4NC 63A handle. Contactors with coil 230V~ - Forced running contactors without automatic return or stop to ensure the test function and repair Tetrapolar 400V~ - References 4 125 53/56/57 can become group head with the connection module for contactor ref. 4 063 02 - I max.: 63A - Contact type: 4 NC - Number of modules: 3. CX³ contactors - with manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 400-400 V

Rated Operating Current 63 A

Control voltage rating (Min-Max) 195-253 V

Operating voltage type AC

Voltage Type (Excitation Voltage) AC

Number of contacts normally opened 0

Number of Normally Closed Contacts 4

Maximum incandescent lamp load 8000 W

Maximum fluorescent lamp load 4700 VA

Maximum fluorescent lamp load (duo circuit) 5000 VA

Maximum fluorescent lamp load (parallel-compensated) 1700 VA

Slider for manual operation Yes
Width in number of modular spaces 3
Installation Depth 44 mm
Additional equipment possible Yes
Protection Class (IP) IP2X
Width 68 mm
Height 94 mm
Depth 53.4 mm
ETIM for 412557 Modular devices for distribution board/surface mounting (EC001653)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
4700 VA
Rated operation current (EF007679)
63 A
Degree of protection (IP) (EF005474)
IP2X
Width in number of modular spacings (EF002950)
3
Max. incandescent lamp load (EF004952)
8000 W
Additional equipment possible (EF008148)
Yes....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412557 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.