

INDUSTRIAL COMPONENT DATA

412558 IME CONTACTOR 25A 2NA 230V SILENC

Brand: IME | Manufacturer Part Number: 412558



Manufacturer	IME
MPN / Reference	412558
Catalog number	412558
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-3F1B249B25
Generated	2026-08-01

Product Overview

CONTACTOR 25A 2NA 230V SILENC

Silent contactor with coil 230V~ - 2P - 250V~/25A - 2 NA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

25A 2NA 230V silencer contactor. Silent coil contactors 230V~ - Forced running contactors without automatic return or stop to ensure the test and repair function Bipolar 250V~ - Max I: 25A - Contact type: 2 NC - Number of modules: 1. CX³ contactors - with manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 250-250 V
Rated Operating Current 25 A
Control voltage rating (Min-Max) 195-253 V
Operating voltage type AC
Voltage Type (Excitation Voltage) AC
Number of contacts normally opened 2
Number of Normally Closed Contacts 0
Maximum incandescent lamp load 3000 W
Maximum fluorescent lamp load 2100 VA
Maximum fluorescent lamp load (duo circuit) 2200 VA
Maximum fluorescent lamp load (parallel-compensated) 2800 VA
Slider for manual operation Yes

Width in number of modular spaces 1

Installation Depth 44 mm

Additional equipment possible Yes

Protection Class (IP) IP2X

Width 17.8 mm

Height 94.9 mm

Depth 66.3 mm

ETIM for 412558 Modular devices for distribution board/surface mounting (EC001653)

Feature Name

Feature Value

Max. load fluorescent lamp (EF004971)

2100 VA

Rated operation current (EF007679)

25 A

Degree of protection (IP) (EF005474)

IP2X

Width in number of modular spacings (EF002950)

1

Max. incandescent lamp load (EF004952)

3000 W

Additional equipment possible (EF008148)

Yes

Max. load fluorescent lamp (parallel compensated) (EF004973)

2800 VA

Max. load fluorescent lamp (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412558 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.