

INDUSTRIAL COMPONENT DATA

412559 IME CONTACTOR 40A 2NA 230V SILENC

Brand: IME | Manufacturer Part Number: 412559



Manufacturer	IME
MPN / Reference	412559
Catalog number	412559
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-6471DD88D3
Generated	2026-08-01

Product Overview

CONTACTOR 40A 2NA 230V SILENC

Silent contactor with coil 230V~ - 2P - 250V~/40A - 2 NA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

Contactor 40A 2NA 230V silencer. Silent coil contactors 230V~ - Forced running contactors without automatic return or stop to ensure the test function and repair Bipolar 250V~ - Max I: 40A - Contact type: 2 NC - Number of modules: 2. CX³ contactors - with manual control - Comply with EN 61095 standard - Accept the passage of the feed comb up to 25A -

Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 250-250 V

Rated Operating Current 40 A

Control voltage rating (Min-Max) 195-253 V

Operating voltage type AC

Voltage Type (Excitation Voltage) AC

Number of contacts normally opened 2

Number of Normally Closed Contacts 0

Maximum incandescent lamp load 5000 W

Maximum fluorescent lamp load 3100 VA

Maximum fluorescent lamp load (duo circuit) 3400 VA

Maximum fluorescent lamp load (parallel-compensated) 1400 VA

Slider for manual operation Yes

Width in number of modular spaces 2
Installation Depth 44 mm
Additional equipment possible Yes
Protection Class (IP) IP2X
Width 68 mm
Height 94 mm
Depth 35.6 mm
ETIM for 412559 Modular devices for distribution board/surface mounting (EC001653)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
3100 VA
Rated operation current (EF007679)
40 A
Degree of protection (IP) (EF005474)
IP2X
Width in number of modular spacings (EF002950)
2
Max. incandescent lamp load (EF004952)
5000 W
Additional equipment possible (EF008148)
Yes
Max. load fluorescent lamp (parallel compensated) (EF004973)
1400 VA
Max. load fluorescent lamp (Duo....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412559 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.