

## INDUSTRIAL COMPONENT DATA

## 413096 IME TRANSF SAFETY 12/24 25VA

Brand: IME | Manufacturer Part Number: 413096



|                 |                  |
|-----------------|------------------|
| Manufacturer    | IME              |
| MPN / Reference | 413096           |
| Catalog number  | 413096           |
| Category        | Bell transformer |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-D48F7A72B4    |
| Generated       | 2026-07-29       |

## Product Overview

TRANSF SAFETY 12/24 25VA

Safety Transformer - 230V/12 or 24V - 25VA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |     |
|--------------|-----|
| Catalog path | IME |
|--------------|-----|

## Additional Product Information

Safety transformer 12/24 25VA. Safety transformers - Comply with EN/IEC 61558-2-6 standard - Protected against overloads and short circuits by CTP - In case of automatic overload cut, interrupt the power and let the transformer cool down before starting it up again - wall mounting or on a symmetrical rail (for 4 modules) 230V/12 or 24V - By 2x12V coupling for ref. 4 130 97 and 4 130 98 with included power strips - P: 25VA - No-load loss: 2.5 W - Voltage drop Cos phi = 1: 29 % - Rend. Cos phi= 1: 66 % - Ucc: 23.3 % - I prim. under load: 0.14A - Number of modules: 4. Transformers, bells and buzzers - Equipped with label holders. Primary voltage 230 V

Secondary Voltage 1 12 V

Secondary Voltage 2 24 V

Maximum power output 25 W

Maximum power loss 2.5 W

Transformer Type Safety Transformer

Surface mounting Yes

Flush mounting Yes

Suitable for series installation Yes

Longitude 72 mm

Width 66 mm  
Height 84 mm  
Width in number of modular spaces 4  
Short circuit protected Yes  
Temperature protection Yes  
With on/off switch No  
ETIM for 413096 Modular devices for distribution board/surface mounting (EC001547)  
Feature Name  
Feature Value  
Temperature protection (EF003782)  
Yes  
Height (EF000040)  
84 mm  
Surface mounting (EF003681)  
Yes  
Width in number of modular spacings (EF002950)  
4  
Primary voltage (EF003775)  
230 V  
Max. power loss (EF004996)  
2.5 W  
Secondary voltage 1 (EF003776)  
12 V  
Short-circuit protected (EF003696)  
Yes  
With on/off switch (EF000488)  
No  
Modular version (EF001126)  
Yes  
Type of transform...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 413096 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.