

INDUSTRIAL COMPONENT DATA

0012622 UNITRONIC EB CY (TP) 4x2x0,75 LAPP UNITRONIC EB CY (TP) 4x2x0,75

Brand: LAPP | Manufacturer Part Number: 0012622

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	LAPP
MPN / Reference	0012622
Catalog number	0012622
Category	Data and communication cable
Minimum order	1 m.
Document ID	EO-4B077E1A0E
Generated	2026-08-03

Product Overview

0012622 UNITRONIC EB CY (TP) 4x2x0,75 LAPP UNITRONIC EB CY (TP) 4x2x0,75

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > flexible data cable transfer from special cable

Additional Product Information

UNITRONIC® EB CY (TP): Low-frequency PVC data cable, DIN 47100 coded, Twisted Pair, Screened, Blue jacket, Intrinsically safe circuits, EN 60079-14/ VDE 0165-1

Hazard protection type -i- is required where there is a risk of explosion

CPR: Article number choice under www.lappkabel.com/cpr

Benefits

Overall braid minimises electrical interference

Decoupling of circuits by means of twisted-pair (TP) design (crosstalk effects)

Application range

Reliable data transmission in intrinsically safe circuits

In EMC-sensitive environments (electromagnetic compatibility)

Product features

For intrinsically safe circuits (type of protection i - intrinsic safety) according to IEC 60079-14:2013 / EN 60079-14:2014 /

VDE 0165-1:2014, section 16.2.2

Flame-retardant according IEC 60332-1-2

Norm references / Approvals

Based on VDE 0812

Product Make-up

Fine-wire strand made of bare copper wires

Core insulation made of PVC

TP structure

Tinned-copper braiding

Outer sheath made of PVC

Outer sheath colour: sky blue (RAL 5015)

Classification ETIM 5

ETIM 5.0 Class-ID: EC000104

ETIM 5.0 Class-Description: Control cable

Classification ETIM 6

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class-Description: Control cable

Core identification code

DIN 47100, refer to Appendix T9

Mutual capacitance

C/C approx. 100 nF/km

C/S approx. 140 nF/km

Inductivity

approx. 0.65 mH/km

Conductor stranding

Strand, fine-wire in accordance with IEC 60228 Cl. 5

Minimum bending radius

Occasional flexing: 15 x outer diameter

Fixed installa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 0012622 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.