

INDUSTRIAL COMPONENT DATA

0027948 ÖLFLEX SERVO FD 796CP 4G1,5+(2x1) LAPP

ÖLFLEX SERVO FD 796 CP 4G1,5+(2x1,0)

Brand: LAPP | Manufacturer Part Number: 0027948



Manufacturer	LAPP
MPN / Reference	0027948
Catalog number	ÖLFLEX SERVO FD 796CP 4G1,5+(2x1)
Category	Power cable 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-138C02A9BB
Generated	2026-08-02

Product Overview

ÖLFLEX SERVO FD 796 CP 4G1,5+(2x1,0)

ÖLFLEX® SERVO FD 796 CP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ÖLFLEX-SERVO cabling

Additional Product Information

ÖLFLEX® SERVO FD 796 CP, shielded servo cable for high dynamic energy chain applications in severe conditions with UL/CSA AWM and VDE certification

Extended Line:

For demanding applications in portable chains. Long hauls or high accelerations

Extended possible product configurations

proceeds

For faster moving processes and thus increases the efficiency of the machines

Suitable for use with servo motor ranges from market-leading manufacturers

Low capacity construction allows for longer cable lengths between converter and drive

Resistant to contact with lubricants based on mineral oil, dilute acids, aqueous alkaline solutions and other chemical agents

Extended temperature range for applications in severe environmental conditions

Copper braid screen acts as protection against electromagnetic interference

Scope of use

Connection cable between the servo controller and the motor

For cable chains or moving parts of machines
For use in pick & place and assembly machinery
Especially suitable for wet areas of machine tools and transfer lines
Assembly lines, production lines, in any type of machinery.

For indoor and outdoor use

Product features

Fire performance: UL/CSA VW-1, FT1 IEC/EN 60332-1-2

Halogen-free materials

Resistant to abrasion and cuts

Oil resistant

Reference Standards / Approvals

Reg. VDE No. 8591 (0027925,.. 926,.. 927,.. 930 in preparation), UL AWM Style 20234, cULus AWM I/II A/B, 1000 V 80°

FT1 CSA AWM I/II A, 1000 V 80° FT1

UL File No. E63634

Use on cable chains: plea...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 0027948 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.