

**INDUSTRIAL COMPONENT DATA**

# 0028186 ÖLFLEX ROBOT 900 P 23G1+(2X1 DP) LAPP ÖLFLEX ROBOT 900 P 23G1+(2X1 DP)

Brand: LAPP | Manufacturer Part Number: 0028186



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | LAPP                                          |
| MPN / Reference | 0028186                                       |
| Catalog number  | ÖLFLEX ROBOT 900 P 23G1+(2X1 DP)              |
| Category        | Power cable less 1 kV, for moving application |
| Minimum order   | 1 m.                                          |
| Document ID     | EO-4C903E6E9B                                 |
| Generated       | 2026-08-06                                    |

## Product Overview

ÖLFLEX ROBOT 900 P 23G1+(2X1 DP)

ÖLFLEX® ROBOT 900 P

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | LAPP > ÖLFLEX ROBOTICS cabling |
|--------------|--------------------------------|

## Additional Product Information

ÖLFLEX® ROBOT 900 P - Power and control cable for bending and torsional load in harsh environmental conditions

Simultaneous bending and torsion

Torsion angle up to +/- 360 °/m

Benefits

Space-saving installation due to small cable diameters

Increased durability under harsh conditions thanks to robust PUR outer sheath

Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media

Wide temperature range for applications in harsh climatic environments

Application range

Industrial machinery and machine tools

Automated handling equipment

Automotive industry

In power chains or moving machine parts

Inside of dresspacks of buckling arm robots and for use for gantry robots

**Product features**

Abrasion and notch-resistant

Flame-retardant

High oil-resistance

Flexible at low temperatures

Low-adhesive surface

Norm references / Approvals

Designed for up to 5 million torsion cycles

For use in power chains: Please comply with assembly guideline Appendix T3

For travel distances up to 10 m

**Product Make-up**

Fine or extra-fine strands made of bare copper wire

Core insulation: TPE

Cores twisted in layers

Versions with additional center pair:

2 cores twisted to a pair, PTFE foil wrapping, layer of tinned copper wires

Wrapping of PTFE tape

PUR outer sheath, black (similar RAL 9005)

Classification ETIM 5

ETIM 5.0 Class-ID: EC000104

ETIM 5.0 Class-Description: Control cable

Classification ETIM 6

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class-De...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 0028186 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.