

INDUSTRIAL COMPONENT DATA

0031067 UNITRONIC 100 CY 5x0,25 LAPP Screened control and signal cable with small cross-sections

Brand: LAPP | Manufacturer Part Number: 0031067



Manufacturer	LAPP
MPN / Reference	0031067
Catalog number	UNITRONIC 100 CY 5x0,25
Category	Data and communication cable
Minimum order	1 m.
Document ID	EO-2D8A87C747
Generated	2026-08-04

Product Overview

UNITRONIC 100 CY 5x0,25

UNITRONIC® 100 CY

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > flexible data cable transfer from special cable

Additional Product Information

UNITRONIC® 100 CY: Low-frequency PVC data cable, LAPP UNITRONIC® core identification code, Screened, Grey, Flame retardant, For various applications

Application range

These control and signal cables are used in the milliampere range for computer systems, electronic control equipment, office machines, balances etc. and wherever the thinnest possible control cables are required.

Product features

Robust, flexible and resistant outer sheath

Small outer diameter despite high number of cores

Cable similar to UNITRONIC® 100, but with copper braiding

Flame-retardant according IEC 60332-1-2

3 cores with earth wire (green-yellow)

2 cores (black/blue)

Norm references / Approvals

Based on: VDE 0814 or VDE 0812

Product Make-up

Fine-wire/multi-wire (0.34 mm²) strand made of bare copper wires

Core insulation made of PVC

Inner sheath made of PVC

For the cross section of 0.14 mm², a polyester tape is used underneath the screen braiding instead of the inner sheath.

Tinned-copper braiding

Outer sheath made of PVC

Outer sheath colour: grey (RAL 7001)

Classification ETIM 5

ETIM 5.0 Class-ID: EC000104

ETIM 5.0 Class-Description: Control cable

Classification ETIM 6

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class-Description: Control cable

Core identification code

Refer to Appendix T7 for the

UNITRONIC® colour codes

Mutual capacitance

Approx. 120 nF/km

Inductivity

approx. 0.7 mH/km

Conductor stranding

Stranded, fine-wire

0.34 mm²: 7-wire

Minimum bending radius

Occasional flexing: 20 x outer diameter

Fix...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 0031067 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.