

## INDUSTRIAL COMPONENT DATA

# 0038062 SERVO LK SEWX STATIC 4G4+(3X1STD) LAPP

## Screened, low capacitive servo cable with PVC outer sheath fo..

Brand: LAPP | Manufacturer Part Number: 0038062



|                 |                                          |
|-----------------|------------------------------------------|
| Manufacturer    | LAPP                                     |
| MPN / Reference | 0038062                                  |
| Catalog number  | SERVO LK SEWX STATIC 4G4+(3X1STD)        |
| Category        | Power cable 1 kV, for moving application |
| Minimum order   | 50 Pcs                                   |
| Document ID     | EO-4C1F2E7DBD                            |
| Generated       | 2026-08-03                               |

## Product Overview

SERVO LK SEWX STATIC 4G4+(3X1STD)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                             |
|--------------|-----------------------------|
| Catalog path | LAPP > ÖLFLEX-SERVO cabling |
|--------------|-----------------------------|

## Additional Product Information

Servomotor cables in acc. to SEW® standard for static use, UL/CSA AWM certified

Servo drives

EMC-compliant

Benefits

Multi-standard certification reduces part varieties and saves costs

Longer cable installation lengths thanks to low mutual capacitance cable design

Copper braiding screens the cable against

electromagnetic interference

Application range

Specially designed to connect SEW servomotors

Connecting cable between servo controller and motor

For static and occasionally flexible use

Industrial machinery and machine tools

Plant engineering  
Product features  
Oil-resistant  
Flame-retardant acc. to IEC 60332-1-2,  
UL VW-1 & CSA FT 1  
Norm references / Approvals  
Based on VDE 0250 / 0285  
UL AWM Style 2570  
UL File No. E63634  
Product Make-up  
Fine-wire, bare copper conductor  
Core insulation: TPE  
Control core triplet with laminated aluminium film and a layer of tinned-copper wires  
Cores twisted in short lay lengths  
Tinned-copper braiding  
PVC outer sheath, orange (RAL 2003)  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000104  
ETIM 5.0 Class-Description: Control cable  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC000104  
ETIM 6.0 Class-Description: Control cable  
Core identification code  
Power: black cores with U, VV, WWW printing and 1 core gnye  
Control cores: black cores with numbers 1, 2 and 3  
Conductor stranding  
Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5  
Minimum bending radius  
Occasional flexing: 15 x outer diameter  
Fixed installation: 4 x outer diameter  
Nominal voltage  
Powe...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 0038062 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.