

INDUSTRIAL COMPONENT DATA

0044015 ÖLFLEX CRANE VS (N)SHTÖU 7G2,5 LAPP ÖLFLEX CRANE VS (N)SHTÖU 7G2,5

Brand: LAPP | Manufacturer Part Number: 0044015



Manufacturer	LAPP
MPN / Reference	0044015
Catalog number	ÖLFLEX CRANE VS (N)SHTÖU 7G2,5
Category	Power cable 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-726FCF4EB5
Generated	2026-08-05

Product Overview

ÖLFLEX CRANE VS (N)SHTÖU 7G2,5

ÖLFLEX® CRANE VS (N)SHTÖU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > Control cables for special applications

Additional Product Information

ÖLFLEX® CRANE VS (N)SHTÖU - Low voltage power cable for outdoor use and crane applications/conveyour technology.

Reelable, U0/U: 0,6/1kV

Reinforced outer sheath design

Central and tear-resistant supporting element

Suitable for extreme tensile stress

Benefits

The central supporting element absorbs the tensile loads that occur, thereby allowing reeling, unreeling and deflection for free-hanging cables even over large distances.

Reeling, unreeling and guiding operations also impose tensile stresses on the cables

Integrated supporting braid prevents undesirable cable twists, and the formation of so-called corkscrew effects

Application range

For use in hoists, transport and conveyer systems

Cables are reeled, unreeled, and guided by roller trains

In dry or damp interiors, outdoors, or not more than 2 weeks without interruption in industrial water

The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3

The assembly and handling guidelines for ÖLFLEX® CRANE cables can be found in the catalogue appendix, technical table T4; for ÖLFLEX® LIFT cables please see the catalogue appendix, technical table T5

Product features

Flame-retardant according IEC 60332-1-2

Oil-resistant according to EN 60811-404

Good chemical, thermal and mechanical-resistance

Norm references / Approvals

Based on VDE 0250-814 (NSHTÖU)

Product Make-up

Strands of tinned-copper wires

Core insulation: rubber compound, type 3GI3

Central supporting element

Suppor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 0044015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.