

**INDUSTRIAL COMPONENT DATA**

# 10080000 EPIC H-B 16 TG 21 ZW LAPP EPIC H-B 16 TG 21 ZW

Brand: LAPP | Manufacturer Part Number: 10080000



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 10080000                           |
| Catalog number  | EPIC H-B 16 TG 21 ZW               |
| Category        | Housing for rectangular connectors |
| Minimum order   | 5 Pcs                              |
| Document ID     | EO-CCAAE5D4BA                      |
| Generated       | 2026-08-04                         |

## Product Overview

EPIC H-B 16 TG 21 ZW

EPIC® H-B 16 TG

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

## Additional Product Information

The robust housing for rectangular connectors with a direct cable entry is suitable for use in lighting and sound systems.

Non-slip ridges for comfortable disconnecting

High version: More interior space for wiring

Protection rating UL50E tested

Benefits

The housing standard. Wide choice for all applications

Application range

Plant engineering

Light &amp; sound technology

Plastics industry

Product features

Hood, low version

Bolts for double lever

Straight cable entry

Versions with / without neck

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating

IP 65 (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10080000 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.