

**INDUSTRIAL COMPONENT DATA**

# 10107900 H-B 24 SDR-LB 21 ZW. BOX MOUNT BASE LAPP

## H-B 24 SDR-LB 21 ZW. BOX MOUNT BASE

Brand: LAPP | Manufacturer Part Number: 10107900



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | LAPP                                |
| MPN / Reference | 10107900                            |
| Catalog number  | H-B 24 SDR-LB 21 ZW. BOX MOUNT BASE |
| Category        | Housing for rectangular connectors  |
| Minimum order   | 5 Pcs                               |
| Document ID     | EO-A7F0D4D94B                       |
| Generated       | 2026-08-05                          |

### Product Overview

H-B 24 SDR-LB 21 ZW. BOX MOUNT BASE  
EPIC® H-B 24 SDR-LB

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

### Additional Product Information

The robust low metal housing with a cable entry and a single lever can be used, for example, in the plastics industry.

Single Lever version for quick locking and simple unlocking with lifting aid

Metal lid with sturdy hinge

Protection rating UL50E tested

Benefits

Safe fixing with 4 screws

Casted neck for easy assembly of the cable gland

Application range

Plant engineering

Light & sound technology

Plastics industry

Product features

Surface-mount base, low version

Single lever

1 cable entry  
Metal cover  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000437  
ETIM 5.0 Class-Description: Housing for industrial connectors  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC000437  
ETIM 6.0 Class-Description: Housing for industrial connectors  
Material  
Housing: powder-coated aluminium alloy, grey  
Lever: zinc-plated steel  
Sealing: NBR  
Protection rating  
IP 65 (latched)  
NEMA 250, UL50E: 12 (latched)  
VDE-tested  
Certified production control: VDE-REG. no.: B437  
UL-tested:  
UL File Number: E75770  
Temperature range  
-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10107900 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.