


INDUSTRIAL COMPONENT DATA**10190000 EPIC H-BE 6 SS DR LAPP EPIC H-BE 6 SS DR**

Brand: LAPP | Manufacturer Part Number: 10190000



Manufacturer	LAPP
MPN / Reference	10190000
Catalog number	EPIC H-BE 6 SS DR
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-ACDD55E4AB
Generated	2026-08-02

Product Overview

EPIC H-BE 6 SS DR

EPIC® H-BE 6 Screw termination

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > EPIC rectangular

Additional Product Information

The multi-functional insert can be used for a broad range of applications, from mechanical engineering and the plastics industry through to lighting and sound systems.

Proven screw for easy installation

Screw, crimp, cage clamp and Push-In version - freely combinable

Made in Germany

Benefits

Standard inserts with screw, crimp cage clamp and Push-In termination

The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents

Railway applications

- Fire protection on railway vehicles: Test according to EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

UL tested for application in control cabinets according to UL 508 / UL 2237

Application range

Mechanical engineering

Plastics industry
Light & sound technology
Railway applications / vehicle construction
Classification ETIM 5
ETIM 5.0 Class-ID: EC000438
ETIM 5.0 Class-Description: Contact insert for industrial connectors
Classification ETIM 6
ETIM 6.0 Class-ID: EC000438
ETIM 6.0 Class-Description: Contact insert for industrial connectors
Rated voltage (V)
IEC: 500 VUL: 600 VCSA: 600 V
Rated impulse voltage
6 kV
Rated current (A)
IEC: 16 A
UL: 16 A
CSA: 16 A
Pollution degree
3
Flammability
UL94 V-0
Contact resistance
< 2 mOhm
Contacts
Copper alloy, hard silver-plated
Number of contacts
6 + PE
Termination methods
Screw termination: 0.5 - 2.5 mm²
Stripping length (mm)
8
Material
PC, polycarbonate
Cycle of mechanical operation
500
Certifications
Tempera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10190000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.