


INDUSTRIAL COMPONENT DATA**10193100 EPIC H-BE 10 BS LAPP EPIC H-BE 10 BS**

Brand: LAPP | Manufacturer Part Number: 10193100



Manufacturer	LAPP
MPN / Reference	10193100
Catalog number	EPIC H-BE 10 BS
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-944E4FEF7B
Generated	2026-08-01

Product Overview

EPIC H-BE 10 BS

EPIC® H-BE 10 Screw termination

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > EPIC rectangular

Additional Product Information

The insert with screw termination can be used for a broad range of applications, for example in lighting and sound systems.

Proven screw for easy installation

Screw, crimp, cage clamp and Push-In version - freely combinable

Made in Germany

Benefits

Standard inserts with screw, crimp cage clamp and Push-In termination

The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents

Railway applications

- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

UL tested for application in control cabinets according UL 508 / UL 2237

Application range

Mechanical engineering

Plastics industry

Light & sound technology

Railway applications / vehicle construction

Classification ETIM 5

ETIM 5.0 Class-ID: EC000438

ETIM 5.0 Class-Description: Contact insert for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

Rated voltage (V)

IEC: 500 VUL: 600 VCSA: 600 V

Rated impulse voltage

6 kV

Rated current (A)

IEC: 16 A

UL: 16 A

CSA: 16 A

Pollution degree

3

Flammability

UL94 V-0

Contact resistance

< 2 mOhm

Contacts

Copper alloy, hard silver-plated

Number of contacts

10 + PE

Termination methods

Screw termination: 0.5 - 2.5 mm²

Stripping length (mm)

8

Material

PC, polycarbonate

Cycle of mechanical operation

500

Certifications

Temperature range

-40°C to +100°C, short-term up t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10193100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.