

INDUSTRIAL COMPONENT DATA

1020058 LAPP ÖLFLEX SERVO 719 CY 4G16+(3x1,5)

Brand: LAPP | Manufacturer Part Number: 1020058



Manufacturer	LAPP
MPN / Reference	1020058
Catalog number	1020058
Category	Power cable 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-9E6622B197
Generated	2026-08-03

Product Overview

ÖLFLEX SERVO 719 CY 4G16+(3x1,5)

ÖLFLEX® SERVO 719 CY

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ÖLFLEX-SERVO cabling

Additional Product Information

Benefits

Suitable for use with servomotor product lines from leading drive manufacturers

Longer cable installation lengths thanks to low mutual capacitance cable design

Multi-standard certification reduces part varieties and saves costs

Space and weight-saving installations due to small cable diameters

Copper braiding screens the cable against
electromagnetic interference

Application range

Connecting cable between servo controller and motor

For static and occasionally flexible use

Plant engineering

Industrial machinery and machine tools

Printing machines

Product features

Low capacitance

Flammability:

UL/CSA: VW-1, FT1

IEC/EN: 60332-1-2

Oil-resistant

EMC-compliant

Norm references / Approvals

USA: UL AWM Style 2570

Canada: cUL AWM Style I/II A/B FT1

UL File No. E63634

Product Make-up

Fine-wire, bare copper conductor

Core insulation: polypropylene (PP)

Individual design depending on the item:

Power cores without or with one or two individually shielded control core pairs twisted together in short lay lengths;

Power cores with control core triplet twisted together in short lay lengths

Tinned copper screen braiding

PVC outer sheath, orange (RAL 2003)

Classification ETIM 5

ETIM 5.0 Class-ID: EC000104

ETIM 5.0 Class-Description: Control cable

Classification ETIM 6

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class-Description: Control cable

Core identification code

Power cores: black with marking U/L1/C/L+; V/L2; W/L3/D /L-; GN/YE protective conductor

Single-paired versions: individual des...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 1020058 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.