


**INDUSTRIAL COMPONENT DATA**

# 10211110 EPIC H-BVE 3 BS LAPP EPIC H-BVE 3 BS

Brand: LAPP | Manufacturer Part Number: 10211110



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | LAPP                                      |
| MPN / Reference | 10211110                                  |
| Catalog number  | EPIC H-BVE 3 BS                           |
| Category        | Contact insert for rectangular connectors |
| Minimum order   | 10 Pcs                                    |
| Document ID     | EO-DBEEA3B28A                             |
| Generated       | 2026-08-01                                |

## Product Overview

EPIC H-BVE 3 BS

EPIC® H-BVE 3

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

## Additional Product Information

The multi-pole insert has delayed switching contacts, which interrupt the power supply of the respective connection before the working contacts are disconnected.

Multipole insert with lagging switch contacts

Switching operations possible for disconnecting under load

Benefits

These high-voltage inserts are additionally equipped with 2 switching contacts

With the relevant wiring, the lagging switch contacts interrupt the power supply before the working contacts are separated

Application range

Plant engineering

Mechanical engineering

Classification ETIM 5

ETIM 5.0 Class-ID: EC000438

ETIM 5.0 Class-Description: Contact insert for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

Rated voltage (V)

IEC: 630 V

UL: 600 V

CSA: 600 V

Rated impulse voltage

6 kV

Rated current (A)

IEC: 16 A

UL: 16 A

CSA: 16 A

Pollution degree

3

Contact resistance

< 2 mOhm

Contacts

Copper alloy, hard silver-plated

Number of contacts

3 + 2 + PE

Termination methods

Screw termination: 0.5 - 2.5 mm<sup>2</sup>

Stripping length (mm)

8

Cycle of mechanical operation

100

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10211110 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.