

INDUSTRIAL COMPONENT DATA

1023290 ÖLFLEX SERVO 7DSL 4G1,5+(2x22AWG) LAPP

ÖLFLEX SERVO 7DSL 4G1,5+(2x22AWG)

Brand: LAPP | Manufacturer Part Number: 1023290



Manufacturer	LAPP
MPN / Reference	1023290
Catalog number	ÖLFLEX SERVO 7DSL 4G1,5+(2x22AWG)
Category	Power cable 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-AF0A886FBD
Generated	2026-08-03

Product Overview

ÖLFLEX SERVO 7DSL 4G1,5+(2x22AWG)

ÖLFLEX® SERVO 7DSL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ÖLFLEX-SERVO cabling

Additional Product Information

ÖLFLEX® SERVO 7DSL - Hybrid servo DSL cable for fixed installation with UL/CUL AWM.

One cable solution for servo drives

Suitable for Hiperface DSL® and SCS open link interfaces

EMC-compliant

Benefits

Only one connection line between drive and motor-feedback system. Instead of the encoder cable a specific integrated data pair takes over the signalling.

Less cables and reduced connection costs

Space and weight savings thanks to hybrid cable design

Multi-standard certification reduces part varieties and saves costs

Easy to install

Application range

For fixed installation or applications with occasional movements

Power drive systems in automation engineering

Connecting cable between servo controller and motor

For use in assembling & pick-and-place machinery

Particularly in wet areas of machine tools and transfer lines

Product features

Maximum DSL transmission length: 100m

Flammability:

UL/CSA: VW-1, FT1

IEC/EN: 60332-1-2

Oil-resistant

Low-capacitance design

EMC-optimised design

Norm references / Approvals

USA: UL AWM Style 2570

Canada: cUL AWM Style I/II A/B FT1

UL File No. E63634

Product Make-up

Fine-wire, bare copper conductor (power cores and control pair) and 7-wire, tinned copper conductor (signal pair)

Core insulation: polypropylene (PP)

Individual design depending on the item: power cores without or with one screened control pair and one DSL data pair twisted together

Tinned-copper braiding

PVC outer sheath, orange (RAL 2003)

Classification ETIM 5

ETIM 5.0 Class-ID: EC000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 1023290 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.