INDUSTRIAL COMPONENT DATA

1026793 ÖLFLEX CHAIN PN 4 X 1,5 LAPP ÖLFLEX CHAIN PN 4 X 1,5

Brand: LAPP | Manufacturer Part Number: 1026793

Manufacturer	LAPP
MPN / Reference	1026793
Catalog number	ÖLFLEX CHAIN PN 4 X 1,5
Category	Power cable less 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-1FA7A51C2B
Generated	2026-08-03

Product Overview

ÖLFLEX CHAIN PN 4 X 1,5
ÖLFLEX® CHAIN PN

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > ÖLFLEX FD cabling

Additional Product Information

ÖLFLEX® CHAIN PN: PROFINET-compliant cable for a wide range of applications in UL/cUL AWM certified energy chains
PROFINET 24 V power cable
Basic Line: Moderate travel lengths and accelerations in energy chain applications.
UL AWM Certification for USA and Canada
proceeds
Compact design
Its multiple certificates allow to reduce the stocks of different products, thus reducing storage costs
Certified for the U.S. and Canada for manufacturers and exporters of machinery, devices, and appliances.
Scope of use
For cable chains or moving parts of machines
For dry and wet interiors
Use in measurement, command and control circuits.
Wiring of machines, tools, devices, appliances and electrical and control cabinets.
Exclusive outdoor use only if protected against UV and within the indicated temperature range

Product features
Designed for a service life of 2 million bending cycles and a horizontal travel distance of up to 10m
Suitable for torsion applications in the "drip loop" of wind turbines (WTG)
Fire performance: UL/CSA VW-1, FT1 IEC/EN 60332-1-2
Oil resistance according to DIN EN 50290-2-22 (TM54)
Low adhesion surface
Reference Standards / Approvals
UL AWM Style 20886
cUL AWM II A/B FT1
UL File No. E63634
Use on cable chains: please pay attention to the assembly guidelines in Appendix T3.
Product composition
Fine bare copper wires
PVC insulation
Layered braided conductors
Nonwoven envelope
Outer Shell: Heat-resistant PVC
Cover Color:
4 conductors: black (RAL 9005),
5 conductors: g...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 1026793 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.