

**INDUSTRIAL COMPONENT DATA**

# 1026793 ÖLFLEX CHAIN PN 4 X 1,5 LAPP ÖLFLEX CHAIN PN 4 X 1,5

Brand: LAPP | Manufacturer Part Number: 1026793



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | LAPP                                          |
| MPN / Reference | 1026793                                       |
| Catalog number  | ÖLFLEX CHAIN PN 4 X 1,5                       |
| Category        | Power cable less 1 kV, for moving application |
| Minimum order   | 1 m.                                          |
| Document ID     | EO-1FA7A51C2B                                 |
| Generated       | 2026-08-05                                    |

## Product Overview

ÖLFLEX CHAIN PN 4 X 1,5

ÖLFLEX® CHAIN PN

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | LAPP > ÖLFLEX FD cabling |
|--------------|--------------------------|

## Additional Product Information

ÖLFLEX® CHAIN PN: PROFINET-compliant cable for a wide range of applications in UL/cUL AWM certified energy chains

PROFINET 24 V power cable

Basic Line: Moderate travel lengths and accelerations in energy chain applications.

UL AWM Certification for USA and Canada

proceeds

Compact design

Its multiple certificates allow to reduce the stocks of different products, thus reducing storage costs

Certified for the U.S. and Canada for manufacturers and exporters of machinery, devices, and appliances.

Scope of use

For cable chains or moving parts of machines

For dry and wet interiors

Use in measurement, command and control circuits.

Wiring of machines, tools, devices, appliances and electrical and control cabinets.

Exclusive outdoor use only if protected against UV and within the indicated temperature range

**Product features**

Designed for a service life of 2 million bending cycles and a horizontal travel distance of up to 10m

Suitable for torsion applications in the "drip loop" of wind turbines (WTG)

Fire performance: UL/CSA VW-1, FT1 IEC/EN 60332-1-2

Oil resistance according to DIN EN 50290-2-22 (TM54)

Low adhesion surface

**Reference Standards / Approvals**

UL AWM Style 20886

cUL AWM II A/B FT1

UL File No. E63634

Use on cable chains: please pay attention to the assembly guidelines in Appendix T3.

**Product composition**

Fine bare copper wires

PVC insulation

Layered braided conductors

Nonwoven envelope

Outer Shell: Heat-resistant PVC

Cover Color:

4 conductors: black (RAL 9005),

5 conductors: g...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send LAPP / 1026793 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.