

## INDUSTRIAL COMPONENT DATA

# 10390411 EPIC MC BUS 2x(4) BCM LAPP EPIC MC BUS 2x(4) BCM

Brand: LAPP | Manufacturer Part Number: 10390411



|                 |                                          |
|-----------------|------------------------------------------|
| Manufacturer    | LAPP                                     |
| MPN / Reference | 10390411                                 |
| Catalog number  | EPIC MC BUS 2x(4) BCM                    |
| Category        | Modular connector (industrial connector) |
| Minimum order   | 10 Pcs                                   |
| Document ID     | EO-B475418321                            |
| Generated       | 2026-08-05                               |

## Product Overview

EPIC MC BUS 2x(4) BCM

EPIC® MC BUS

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path LAPP &gt; EPIC rectangular

## Additional Product Information

Shielded module for data transmission, category 5e up to gigabit/s, crimped terminal for permanent contact with anti-vibration protection, cable fastening 3 - 9 mm

Shielded module for the transmission of data and signals. Ethernet category 5e suitable proceeds

Shielded module for the transmission of data and signals. Ethernet category 5e suitable

Crimp connection for permanent vibration proof contacting

CAT5e up to 1 Gigabit/s

cable clamp 3 - 9 mm

The combination of different functions in one connector ensures high flexibility

Scope of use

Machine building

Robotics industry

Plant Engineering

Renewable energy

ETS Classification 5  
ETIM 5.0 Class-ID: EC002641  
ETIM Class 5.0 Description: Modular Connector (Industrial Connector)  
ETIM Rating 6  
ETIM 6.0 Class-ID: EC002641  
ETIM 6.0 Class-Description: modular connector (industrial connector)  
Nominal voltage  
50  
Voltage test  
0.8 kV  
Rated current in A  
10  
Degree of contamination  
3  
Number of contacts  
8  
Connection type  
Crimped terminal: 0.14 - 2.5 mm<sup>2</sup>  
Material  
PA  
Connection cycles  
500  
Temperature range  
-40°C  
+125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10390411 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.