

INDUSTRIAL COMPONENT DATA

10400300 H-BE 24 SF MALE INSERT W. CLAMP SPRING LAPP

H-BE 24 SF MALE INSERT W. CLAMP SPRING

Brand: LAPP | Manufacturer Part Number: 10400300



Manufacturer	LAPP
MPN / Reference	10400300
Catalog number	H-BE 24 SF MALE INSERT W. CLAMP SPRING
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-839F58A49C
Generated	2026-08-04

Product Overview

H-BE 24 SF MALE INSERT W. CLAMP SPRING

EPIC® H-BE 24 Cage clamp

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > EPIC rectangular
--------------	-------------------------

Additional Product Information

The connector insert with spring-type terminal is ideal for mechanical engineering, is highly reliable and suitable for higher voltages and currents.

Multifunctional insert for versatile applications

Screw, crimp, cage clamp and Push-In version - freely combinable

Also as EPIC® H-BE 48 available

Benefits

Standard inserts with screw, crimp cage clamp and Push-In termination

The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents

Application range

Mechanical engineering

Light & sound technology

Plastics industry

Classification ETIM 5

ETIM 5.0 Class-ID: EC000438
ETIM 5.0 Class-Description: Contact insert for industrial connectors
Classification ETIM 6
ETIM 6.0 Class-ID: EC000438
ETIM 6.0 Class-Description: Contact insert for industrial connectors
Rated voltage (V)
IEC: 500 VUL: 600 VCSA: 600 V
Rated impulse voltage
6 kV
Rated current (A)
IEC: 16 A
UL: 16 A
CSA: 16 A
Pollution degree
3
Flammability
UL94 V-2
Contact resistance
1.5 - 4 mohm
Contacts
Copper alloy, hard silver-plated
Number of contacts
24 + PE
Termination methods
Cage clamp termination: 0.5 - 2.5 mm²
Stripping length (mm)
7
Cycle of mechanical operation
100
Certifications
UL-tested:
UL File Number: E75770
Temperature range
-40°C to +100°C, short-term up to +125°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10400300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.