


INDUSTRIAL COMPONENT DATA

10401000 H-BE 6 BF FEMALE INSERT W. CLAMP SPRING

LAPP H-BE 6 BF FEMALE INSERT W. CLAMP SPRING

Brand: LAPP | Manufacturer Part Number: 10401000



Manufacturer	LAPP
MPN / Reference	10401000
Catalog number	H-BE 6 BF FEMALE INSERT W. CLAMP SPRING
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-7C74C04134
Generated	2026-08-01

Product Overview

H-BE 6 BF FEMALE INSERT M.KLEMMFEDER
EPIC® H-BE 6 Cage clamp

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > EPIC rectangular
--------------	-------------------------

Additional Product Information

The multi-functional insert with spring-type terminal for rectangular connectors is suitable for use in the plastics industry as it ensures high reliability.

Vibration resistant and fast wire connection

Screw, crimp, cage clamp and Push-In version - freely combinable

Benefits

Standard inserts with screw, crimp cage clamp and Push-In termination

The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents

Application range

Mechanical engineering

Light & sound technology

Plastics industry

Classification ETIM 5

ETIM 5.0 Class-ID: EC000438

ETIM 5.0 Class-Description: Contact insert for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

Rated voltage (V)

IEC: 500 VUL: 600 VCSA: 600 V

Rated impulse voltage

6 kV

Rated current (A)

IEC: 16 A

UL: 16 A

CSA: 16 A

Pollution degree

3

Flammability

UL94 V-2

Contact resistance

1.5 - 4 mohm

Contacts

Copper alloy, hard silver-plated

Number of contacts

6 + PE

Termination methods

Cage clamp termination: 0.5 - 2.5 mm²

Stripping length (mm)

7

Material

PC, polycarbonate

Cycle of mechanical operation

100

Certifications

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10401000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.