

INDUSTRIAL COMPONENT DATA

10421000 EPIC H-A 3 BS LAPP EPIC H-A 3 BS

Brand: LAPP | Manufacturer Part Number: 10421000



Manufacturer	LAPP
MPN / Reference	10421000
Catalog number	EPIC H-A 3 BS
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-97FE527B9E
Generated	2026-08-02

Product Overview

EPIC H-A 3 BS

EPIC® H-A 3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > EPIC rectangular
--------------	-------------------------

Additional Product Information

The small, robust insert is suitable for power supply connectors and can be also used, for example, in machine or device manufacturing or in control systems.

Small power connector for single- or three-phase current

easy to assemble due to straight entry of conductors

Made in Germany

Benefits

The small H-A 3 / H-A 4 are used whenever there is minimal space.

Easy to service screw connection

Easy cable connection with strait cable entry in the contacts

Railway applications

- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

Application range

Machine and equipment manufacturing

Control engineering

Apparatus construction

Railway applications / vehicle construction

Classification ETIM 5

ETIM 5.0 Class-ID: EC000438

ETIM 5.0 Class-Description: Contact insert for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

Rated voltage (V)

IEC: 400 V

UL: 600 V

CSA: 600 V

Rated impulse voltage

4 kV

Rated current (A)

IEC: 23 A

UL: 10 A

CSA: 10 A

Pollution degree

3

Flammability

UL94 V-0

Contact resistance

1.5 - 4 mohm

Contacts

Copper alloy, hard silver-plated

Number of contacts

3 + PE

Termination methods

Screw termination: 0.5 - 2.5 mm² (2.5 mm² with conductor end sleeves depending on the crimping profile)

Stripping length (mm)

6

Cycle of mechanical operation

100

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

U...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10421000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.