

INDUSTRIAL COMPONENT DATA

10423203 ULTRA H-A 3 AGSV OPEN LAPP EPIC ULTRA H-A 3 AGSV open

Brand: LAPP | Manufacturer Part Number: 10423203



Manufacturer	LAPP
MPN / Reference	10423203
Catalog number	ULTRA H-A 3 AGSV OPEN
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-E3548426EC
Generated	2026-08-04

Product Overview

EPIC ULTRA H-A 3 AGSV open

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > EPIC rectangular
--------------	-------------------------

Additional Product Information

EPIC® Rectangular connector housing EMC protection, corrosion resistant, UL50E, Nema250

EMC protection

Corrosion-resistant

Made in Germany

Benefits

Optimum, low-resistance 360° screening

All-purpose due to high corrosion resistance and high environmental protection.

Space-saving due to compact dimensions

High mechanical and chemical resistance

Application range

In EMC-sensitive environments

For fixed and flexible applications (e.g. machinery building, wind turbines)

Construction machinery

Electric motor manufacturing

Product features

Panel-mount base with open base, side cable entry and additional side M20 thread
Resistance to cyclic salt spray is tested according to IEC 68-2-52, severity level 2
Salt spray testing according to DIN EN ISO 9227, method NSS, period of test 480 hours
Corrosion-resistant according to DIN EN 6988
Delivery including stainless steel screw for the inserts
Classification ETIM 5
ETIM 5.0 Class-ID: EC000437
ETIM 5.0 Class-Description: Housing for industrial connectors
Classification ETIM 6
ETIM 6.0 Class-ID: EC000437
ETIM 6.0 Class-Description: Housing for industrial connectors
Material
Housing: nickel-plated zinc diecasting
Lever: stainless steel
Sealing: NBR
Protection rating
IP 65
NEMA 250, UL50E: 12, 4, 4X (latched)
VDE-tested
Certified production control: VDE-REG. no.: B437
UL-tested:
UL File Number: E75770
Temperature range
-40°C to +100°C, short-term up to +125°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10423203 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.