

INDUSTRIAL COMPONENT DATA

10423204 EPIC ULTRA H-A 3 TBF M20 LAPP EPIC ULTRA H-A 3 TBF M20

Brand: LAPP | Manufacturer Part Number: 10423204



Manufacturer	LAPP
MPN / Reference	10423204
Catalog number	EPIC ULTRA H-A 3 TBF M20
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-99D28C3712
Generated	2026-08-02

Product Overview

EPIC ULTRA H-A 3 TBF M20

EPIC® ULTRA H-A 3 TBF

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > EPIC rectangular
--------------	-------------------------

Additional Product Information

EPIC® Rectangular connector housing EMC protection, corrosion resistant, UL50E, Nema250

EMC protection

Corrosion-resistant

Made in Germany

Benefits

Plugable with standard housings

Optimum, low-resistance 360° screening

All-purpose due to high corrosion resistance and high environmental protection.

Space-saving due to compact dimensions

High mechanical and chemical resistance

Application range

In EMC-sensitive environments

For fixed and flexible applications (e.g. machinery building, wind turbines)

Construction machinery

Electric motor manufacturing

Product features

Resistance to cyclic salt spray is tested according to IEC 68-2-52, severity level 2

Salt spray testing according to DIN EN ISO 9227, method NSS, period of test 480 hours

Corrosion-resistant according to DIN EN 6988

Delivery including stainless steel screw for the inserts

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: nickel-plated zinc diecasting

Lever: stainless steel

Sealing: NBR

Protection rating

IP 65

NEMA 250, UL50E: 12, 4, 4X (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10423204 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.