


**INDUSTRIAL COMPONENT DATA**

# 10424000 H-A 3 AGSV 11 ZW. BOX MOUNT BASE LAPP H-A 3 AGSV 11 ZW. BOX MOUNT BASE

Brand: LAPP | Manufacturer Part Number: 10424000



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 10424000                           |
| Catalog number  | H-A 3 AGSV 11 ZW. BOX MOUNT BASE   |
| Category        | Housing for rectangular connectors |
| Minimum order   | 10 Pcs                             |
| Document ID     | EO-06F48EE058                      |
| Generated       | 2026-08-04                         |

## Product Overview

H-A 3 AGSV 11 ZW. BOX MOUNT BASE  
EPIC® H-A 3 AGSV

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

## Additional Product Information

The robust compact base housing consists of one lever and a cable entry and is ideal for supplying power in restricted spaces.

Lightweight, chemically resistant plastic housing

Protection rating UL50E tested

Benefits

Housing in plastic or metal version for safe connections in the smallest possible space

Application range

Machine and equipment manufacturing

Control engineering

Electronic laboratory

Product features

Surface-mount base

1 lever

1 cable entry

Versions with / without cable gland

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: powder-coated zinc die-casting, grey

Lever: zinc-plated steel

Sealing: NBR

Housing: grey thermoplastic, black

Lever: zinc-plated steel

Sealing: NBR

Protection rating

IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10424000 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.