

**INDUSTRIAL COMPONENT DATA**

# 10429200 H-A 3 TGVB 11 N.GEW. CABLE COUPLER HOOD

## LAPP H-A 3 TGVB 11 N.GEW. CABLE COUPLER HOOD

Brand: LAPP | Manufacturer Part Number: 10429200



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | LAPP                                    |
| MPN / Reference | 10429200                                |
| Catalog number  | H-A 3 TGVB 11 N.GEW. CABLE COUPLER HOOD |
| Category        | Housing for rectangular connectors      |
| Minimum order   | 10 Pcs                                  |
| Document ID     | EO-1B4099F995                           |
| Generated       | 2026-08-03                              |

### Product Overview

H-A 3 TGVB 11 N.GEW. CABLE COUPLER HOOD

EPIC® H-A 3 TGVB

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      LAPP > EPIC rectangular

### Additional Product Information

The robust plastic cable coupler hood for rectangular connectors with a direct cable entry and one lever is ideal for use in control systems.

Lightweight, chemically resistant plastic housing

Protection rating UL50E tested

Benefits

Housing in plastic or metal version. For power supply in the smallest possible space

Application range

Machine and equipment manufacturing

Control engineering

Electronic laboratory

Product features

Cable coupler hood

1 lever

Straight cable entry

Versions with / without cable gland

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

thermoplastic, grey, black

Lever: zinc-plated steel

Protection rating

IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 10429200 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.