INDUSTRIAL COMPONENT DATA

1120237 ÖLFLEX CLASSIC 110 Black 0,6/1kV 5G0,75 LAPP ÖLFLEX CLASSIC 110 Black 0,6/1kV 5G0,75

Brand: LAPP | Manufacturer Part Number: 1120237



Manufacturer	LAPP
MPN / Reference	1120237
Catalog number	ÖLFLEX CLASSIC 110 Black 0,6/1kV 5G0,75
Category	Power cable 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-C6C2086241
Generated	2026-11-19

Product Overview

ÖLFLEX CLASSIC 110 Black 0,6/1kV 5G0,75
ÖLFLEX® CLASSIC 110 BLACK 0,6/1 kV

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > ÖLFLEX PVC, numbered cores

Additional Product Information

ÖLFLEX® CLASSIC 110 BLACK 0,6/1kV: power and control cable for various applications, PVC, conductor class 5, black cores, number coded, outdoors
Good outdoor performance
CPR: Article number choice under www.lappkabel.com/cpr
Application range
Plant engineering
Industrial machinery
Heating and air-conditioning systems
Power stations
Stage applications
For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
Each dimension with nominal/ minimum average wall thickness of the outer sheath of at least 1.8 mm: For applications where a strengthened outer sheath may turn out to be advantageous
Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product features
Flame-retardant according IEC 60332-1-2
UV and weather-resistant according to ISO 4892-2
Ozone-resistant according to EN 50396
Norm references / Approvals
Based on VDE 0250-1 and HD 627-1 S1
Product Make-up
Fine-wire strand made of bare copper wires
PVC insulation LAPP P8/1
PVC outer sheath, black (RAL 9005)
Classification ETIM 5
ETIM 5.0 Class-ID: EC000104
ETIM 5.0 Class-Description: Control cable
Classification ETIM 6
ETIM 6.0 Class-ID: EC000104
ETIM 6.0 Class-Description: Control cable
Core identification code
Black with white numbers acc. to VDE 0293-334
Conductor stranding
Fine wire according to VDE 0295,
class 5/IEC 60228 class 5
Torsion movement in WTG
TW-0 & TW-1, refer to Appendix T0
Minimum bending radius
St...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 1120237 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.