

INDUSTRIAL COMPONENT DATA

1123033 ÖLFLEX CLASSIC 130 H 3G0,75 LAPP ÖLFLEX CLASSIC 130 H 3G0,75

Brand: LAPP | Manufacturer Part Number: 1123033



Manufacturer	LAPP
MPN / Reference	1123033
Catalog number	ÖLFLEX CLASSIC 130 H 3G0,75
Category	Power cable less 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-11BAA0F377
Generated	2026-08-01

Product Overview

ÖLFLEX CLASSIC 130 H 3G0,75

ÖLFLEX® CLASSIC 130 H

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ÖLFLEX environment, numbered cores

Additional Product Information

ÖLFLEX® CLASSIC 130 H - halogen-free control cable, HFFR and flexible for various applications, U0/U: 300/500V

CPR: Article number choice under www.lappkabel.com/cpr

For use within public buildings and industrial plants

Benefits

Easy handling and installation due to flexible design

Certified for maritime applications

Application range

Public buildings like airports or railway stations

Plant engineering, Industrial machinery

Heating and air-conditioning systems

Stage applications

Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards

Note: for the use of AWM (Appliance Wiring Material) cables in industrial machinery (USA) according to NFPA 79: please see the catalogue appendix table T29

Product features

Flame-retardant according to IEC 60332-1-2

(flame spread on a single cable)

No flame-propagation according to IEC 60332-3-22 and IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle)

Halogen-free according to IEC 60754-1

(amount of halogen acid gas)

Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)

Low smoke density according to IEC 61034-2

Norm references / Approvals

UL AWM style 21217

Based on EN 50525-3-11

Based on EN 50525-2-51

DNV GL certificate no. TAE00002RJ

Product Make-up

Fine-wire strand made of bare copper wires

Core insulation: Halogen-free

Cores twisted in layers

Outer sheath: Special halogen-free compound, grey (similar to RAL 7001)

Classifica...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 1123033 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.