

INDUSTRIAL COMPONENT DATA

1123422 ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 7G1,5 LAPP

ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 7G1,5

Brand: LAPP | Manufacturer Part Number: 1123422



Manufacturer	LAPP
MPN / Reference	1123422
Catalog number	ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 7G1,5
Category	Power cable 1 kV, for moving application
Minimum order	1 m.
Document ID	EO-FB2ADCFE5E
Generated	2026-08-04

Product Overview

ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 7G1,5

ÖLFLEX® CLASSIC 130 H BK 0,6/1 kV

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ÖLFLEX environment, numbered cores

Additional Product Information

ÖLFLEX® CLASSIC 130 H BK 0,6/1 kV Power and Control Cable UL AWM Style 21156, Conductor class 5, Halogen-free/

Highly Flame Retardant, Public buildings, Outdoor

CPR: Article number choice under www.lappkabel.com/cpr

Public buildings

UL AWM recognized

Benefits

Easy handling and installation due to flexible design

Application range

Plant engineering

Industrial machinery

Heating and air-conditioning systems

Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards

For outdoor applications

According to NFPA 79, subchapter 12.9.2: Use for industrial machinery operated in the USA on the basis of UL AWM

(recognized) certification

Each dimension with nominal/ minimum average wall thickness of the outer sheath of at least 1.8 mm: For applications where a strengthened outer sheath may turn out to be advantageous

Product features

Flame-retardant according to IEC 60332-1-2

(flame spread on a single cable)

No flame-propagation according to IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle)

Halogen-free according to IEC 60754-1

(amount of halogen acid gas)

Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)

Low smoke density according to IEC 61034-2

UV and weather-resistant according to ISO 4892-2

Ozone-resistant according to EN 50396

Norm references / Approvals

Based on EN 50525-3-11

UL AWM approval: refer to data sheet

Product Make-up

Fine-wire strand made of bare copp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 1123422 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.