

**INDUSTRIAL COMPONENT DATA**

# 11252500 H-D 8 SCM MALE INSERT LAPP H-D 8 SCM MALE INSERT

Brand: LAPP | Manufacturer Part Number: 11252500



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | LAPP                                      |
| MPN / Reference | 11252500                                  |
| Catalog number  | H-D 8 SCM MALE INSERT                     |
| Category        | Contact insert for rectangular connectors |
| Minimum order   | 10 Pcs                                    |
| Document ID     | EO-7A135A74D4                             |
| Generated       | 2026-08-01                                |

## Product Overview

H-D 8 SCM MALE INSERT  
EPIC® H-D 8

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; EPIC rectangular

## Additional Product Information

The powerful and compact standard insert has PE contacts with screw termination and is suitable, for example, for control systems.

Compact, powerful standard insert

For machined contacts for fast processing with the crimping tool

Made in Germany

Benefits

Small, high-performance connector

High performance crimping contacts

PE contact with screw connection

Application range

Machine and equipment manufacturing

Control engineering

Classification ETIM 5

ETIM 5.0 Class-ID: EC000438

ETIM 5.0 Class-Description: Contact insert for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

Rated voltage (V)

IEC: 24 V (AC)/60 V (DC) metal housing; 250 V thermoplastic housing;

UL: 250 V

Rated impulse voltage

2.5 kV

Rated current (A)

IEC: 10 A

UL: 10 A

Pollution degree

3

Flammability

UL94 V-0

Contact resistance

< 2 mOhm

Contacts

Copper alloy, hard silver/gold-plated

Number of contacts

8

Termination methods

Crimp termination: 0.14 - 2.5 mm<sup>2</sup>

Material

PBT Polyester

Cycle of mechanical operation

100

Certifications

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 11252500 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.