

## INDUSTRIAL COMPONENT DATA

# 11285200 EPIC H-DD 72 SCM 1-72 MALE INSERT LAPP EPIC H-DD 72 SCM 1-72 MALE INSERT

Brand: LAPP | Manufacturer Part Number: 11285200



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | LAPP                                      |
| MPN / Reference | 11285200                                  |
| Catalog number  | EPIC H-DD 72 SCM 1-72 MALE INSERT         |
| Category        | Contact insert for rectangular connectors |
| Minimum order   | 5 Pcs                                     |
| Document ID     | EO-9BCC1DA44E                             |
| Generated       | 2026-08-05                                |

## Product Overview

EPIC H-DD 72 SCM 1-72 MALE INSERT

EPIC® H-DD 72

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path LAPP &gt; EPIC rectangular

## Additional Product Information

## Benefits

The H-DD series with machined contacts is designed for a high number of pins in very tight spaces. This allows for smaller housing types to be chosen.

## Application range

Mechanical engineering

Light &amp; sound technology

Plastics industry

## Classification ETIM 5

ETIM 5.0 Class-ID: EC000438

ETIM 5.0 Class-Description: Contact insert for industrial connectors

## Classification ETIM 6

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

## Rated voltage (V)

IEC: 250 V  
UL: 600 V  
CSA: 600 V  
Rated impulse voltage  
2.5 kV  
Rated current (A)  
IEC: 10 A  
UL: 8.5 A  
CSA: 10 A  
Pollution degree  
2  
Contact resistance  
< 3 mOhm  
Contacts  
Copper alloy, hard silver/gold-plated  
Number of contacts  
72 + PE  
Termination methods  
Crimp termination: 0.14 - 2.5 mm<sup>2</sup>  
Cycle of mechanical operation  
100  
VDE-tested  
Certified production control: VDE-REG. no.: B437  
UL-tested:  
UL File Number: E75770  
Temperature range  
-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 11285200 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.