

INDUSTRIAL COMPONENT DATA

1308210 LAPP ÖLFLEX 408 P 10G1

Brand: LAPP | Manufacturer Part Number: 1308210



Manufacturer	LAPP
MPN / Reference	1308210
Catalog number	1308210
Category	Contact insert for circular connectors
Minimum order	1 m.
Document ID	EO-7175F093A6
Generated	2026-08-02

Product Overview

ÖLFLEX 408 P 10G1

ÖLFLEX® 408 P

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > ÖLFLEX PUR/TPE numbered cores
--------------	--------------------------------------

Additional Product Information

Benefits

Increased durability under harsh conditions thanks to robust PUR outer sheath

Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media

Interstice-filling functional layer ensures more safety and efficiency during industrial and manual jacket stripping

VDE-tested characteristics

Good combination of quality and price

Application range

Appliance and apparatus construction

Industrial machinery and machine tools

Measurement, control and electrical applications

Very suitable for oily wet areas within machinery and production lines that are subject to normal mechanical stress

Under consideration of the temperature range also suitable for outdoor use

Product features

High oil-resistance

Abrasion and notch-resistant
Low-adhesive surface
Resistant to hydrolysis and microbes
Norm references / Approvals
VDE Reg.No. 8744
Product Make-up
Fine-wire, bare copper conductor
Core insulation: special PVC
Cores twisted in layers
Special outer sheath of polyurethane with interstice-filling functional layer
Sheath colour: Grey (similar RAL 7001)
Classification ETIM 5
ETIM 5.0 Class-ID: EC000104
ETIM 5.0 Class-Description: Control cable
Classification ETIM 6
ETIM 6.0 Class-ID: EC000104
ETIM 6.0 Class-Description: Control cable
Core identification code
Black with white numbers acc. to VDE 0293-334
Conductor stranding
Fine wire according to VDE 0295,
class 5/IEC 60228 class 5
Minimum bending radius
Flexible use: 12.5 x ou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 1308210 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.