


INDUSTRIAL COMPONENT DATA

15315015 ÖLFLEX TRAIN 315 C TW-P 300V 2X1,5 LAPP

ÖLFLEX TRAIN 315 C TW-P 300V 2X1,5

Brand: LAPP | Manufacturer Part Number: 15315015



Manufacturer	LAPP
MPN / Reference	15315015
Catalog number	ÖLFLEX TRAIN 315 C TW-P 300V 2X1,5
Category	Power cable less 1 kV, for permanent installation
Minimum order	1 m.
Document ID	EO-A7F54DBF9B
Generated	2026-08-04

Product Overview

ÖLFLEX TRAIN 315 C TW-P 300V 2X1,5

ÖLFLEX® TRAIN 315 C TW-P 300V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ÖLFLEX TRAIN

Additional Product Information

ÖLFLEX® TRAIN 315 C TW-P 300V - control cable shielded according to EN 50306-4 3P type MM S, 300/500V for rail vehicles/trains, EN 45545: HL1-HL3, NF F 16-101: C/F0

Meets EN 50306-4 class P, type MM S and EN 45545-2

High temperature resistance: -50°C up to +125°C

Highly oil- and fuel-resistant

Benefits

Reduced insulation wall thickness, thus space-saving installation

Copper screening complies with EMC requirements and protects against electromagnetic interference

Resistant to mechanical influences in harsh environmental conditions

Extended temperature range

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

Application range

In EMC-sensitive environments

For use in railway vehicles, for fixed and protected installation and applications where limited movement may occur

Suitable for control and monitoring circuits as well as locking circuits and internal wiring of equipment in trains and locomotives

Also applicable within oily environments and areas with increased ambient temperature

Product features

Fire behaviour according to EN/IEC:

- Halogen-free acc. to EN 60754-1
- No corrosive gases acc. to EN 60754-2
- No fluorine acc. to EN 60684-2
- No toxic gases acc. to EN 50305
- Low smoke density acc. to EN 61034-2
- Flame-retardant acc. to EN 60332-1-2
- No flame propagation acc. to EN 60332-3-24 / EN 60332-3-25 / EN 50305

Fire behaviour according to NF:

- Toxicity of gases acc. to NF X 70-100
- Low smoke density acc. t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 15315015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.