


INDUSTRIAL COMPONENT DATA

15315016 ÖLFLEX TRAIN 315 C TW-P 300V 3X1,5 LAPP

ÖLFLEX TRAIN 315 C TW-P 300V 3X1,5

Brand: LAPP | Manufacturer Part Number: 15315016



Manufacturer	LAPP
MPN / Reference	15315016
Catalog number	ÖLFLEX TRAIN 315 C TW-P 300V 3X1,5
Category	Power cable less 1 kV, for permanent installation
Minimum order	1 m.
Document ID	EO-D25D6F2495
Generated	2026-08-04

Product Overview

ÖLFLEX TRAIN 315 C TW-P 300V 3X1,5

ÖLFLEX® TRAIN 315 C TW-P 300V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LAPP > ÖLFLEX TRAIN**

Additional Product Information

Benefits

Reduced insulation wall thickness, thus space-saving installation

Copper screening complies with EMC requirements and protects against electromagnetic interference

Resistant to mechanical influences in harsh environmental conditions

Extended temperature range

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

Application range

In EMC-sensitive environments

For use in railway vehicles, for fixed and protected installation and applications where limited movement may occur

Suitable for control and monitoring circuits as well as locking circuits and internal wiring of equipment in trains and locomotives

Also applicable within oily environments and areas with increased ambient temperature

Product features

Fire behaviour according to EN/IEC:

- Halogen-free acc. to EN 60754-1
 - No corrosive gases acc. to EN 60754-2
 - No fluorine acc. to EN 60684-2
 - No toxic gases acc. to EN 50305
 - Low smoke density acc. to EN 61034-2
 - Flame-retardant acc. to EN 60332-1-2
 - No flame propagation acc. to
EN 60332-3-24 / EN 60332-3-25 /
EN 50305
- Fire behaviour according to NF:
- Toxicity of gases acc. to NF X 70-100
 - Low smoke density acc. to NF X 10-702
 - No flame propagation acc. to NF C 32-070,
Cat. C1 and C2
- Chemical properties:
- Oil resistant acc. to EN 50306
 - Fuel resistant acc. to EN 50306
 - Acid resistant acc. to EN 50306
 - Alkali resistant acc. to EN 50306
 - Ozone resistant acc. to EN 50306
- Current rating according to E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 15315016 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.