

## INDUSTRIAL COMPONENT DATA

**15317013 ÖLFLEX TRAIN 317 C TW-P 300V 3X(2X1,5) LAPP**  
**ÖLFLEX TRAIN 317 C TW-P 300V 3X(2X1,5)**

Brand: LAPP | Manufacturer Part Number: 15317013



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | LAPP                                              |
| MPN / Reference | 15317013                                          |
| Catalog number  | ÖLFLEX TRAIN 317 C TW-P 300V 3X(2X1,5)            |
| Category        | Power cable less 1 kV, for permanent installation |
| Minimum order   | 1 m.                                              |
| Document ID     | EO-24A536D43B                                     |
| Generated       | 2026-08-05                                        |

**Product Overview**

ÖLFLEX TRAIN 317 C TW-P 300V 3X(2X1,5)

ÖLFLEX® TRAIN 317 C TW-P 300V

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path LAPP &gt; ÖLFLEX TRAIN

**Additional Product Information**

ÖLFLEX® TRAIN 317 C TW-P 300V - control cable shielded according to EN 50306-4 5P type MM S, 300/500V for rail vehicles/trains, EN 45545: HL1-HL3, NF F 16-101: C/F1

Meets EN 50306-4 class P, type MM S and EN 45545-2

High temperature resistance: -50°C up to +125°C

Highly oil- and fuel-resistant

Benefits

Reduced insulation wall thickness, thus space-saving installation

Copper screening complies with EMC requirements and protects against electromagnetic interference

Resistant to mechanical influences in harsh environmental conditions

Extended temperature range

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

Application range

In EMC-sensitive environments

For use in railway vehicles, for fixed and protected installation and applications where limited movement may occur

Suitable for control and monitoring circuits as well as locking circuits and internal wiring of equipment in trains and locomotives

Also applicable within oily environments and areas with increased ambient temperature

Product features

Fire behaviour according to EN/IEC:

- Halogen-free acc. to EN 60754-1
- No corrosive gases acc. to EN 60754-2
- No fluorine acc. to EN 60684-2
- No toxic gases acc. to EN 50305
- Low smoke density acc. to EN 61034-2
- Flame-retardant acc. to EN 60332-1-2
- No flame propagation acc. to EN 60332-3-24 / EN 60332-3-25 / EN 50305

Fire behaviour according to NF:

- Toxicity of gases acc. to NF X 70-100
- Low smoke density acc. t...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 15317013 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.