

**INDUSTRIAL COMPONENT DATA**

# 15345025 ÖLFLEX TRAIN 345 C 600V 3G1,5 LAPP ÖLFLEX TRAIN 345 C 600V 3G1,5

Brand: LAPP | Manufacturer Part Number: 15345025



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | LAPP                                            |
| MPN / Reference | 15345025                                        |
| Catalog number  | ÖLFLEX TRAIN 345 C 600V 3G1,5                   |
| Category        | Power cable >= 1 kV, for permanent installation |
| Minimum order   | 1 m.                                            |
| Document ID     | EO-15AC319687                                   |
| Generated       | 2026-08-03                                      |

## Product Overview

ÖLFLEX TRAIN 345 C 600V 3G1,5

ÖLFLEX® TRAIN 345 C 600V

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; ÖLFLEX TRAIN

## Additional Product Information

**Benefits**

Copper screening complies with EMC requirements and protects against electromagnetic interference

Good chemical resistance please see Appendix T1

Resistant to mechanical influences in harsh environmental conditions

Extended temperature range

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

Application range

For use in railway vehicles, for fixed installations and applications where limited movement may occur

Suitable for connecting lamps, heating equipment, switchgear, terminal boxes and power supply

Also applicable within oily environments and areas with increased ambient temperature

**Product features**

Fire behaviour according to EN/IEC:

- Halogen-free acc. to EN 60754-1

- No corrosive gases acc. to EN 60754-2

- No fluorine acc. to EN 60684-2
- No toxic gases acc. to EN 50305
- Low smoke density acc. to EN 61034-2
- Flame-retardant acc. to EN 60332-1-2
- No flame propagation acc. to EN 60332-3-24 / EN 60332-3-25 / EN 50305

Fire behaviour according to NF:

- Toxicity of gases acc. to NF X 70-100
- Low smoke density acc. to NF X 10-702
- No flame propagation acc. to NF C 32-070, Cat. C1 and C2

Chemical properties:

- Oil resistant acc. to EN 50264-3-2
- Fuel resistant acc. to EN 50264-3-2
- Acid resistant acc. to EN 50264-3-2
- Alkali resistant acc. to EN 50264-3-2
- Ozone resistant acc. to EN 50264-3-2/ EN 50305)

Current rating according to EN 50355, appendix A

Norm references / Approvals

EN 50264-3-2 type MM...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 15345025 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.