

INDUSTRIAL COMPONENT DATA

15350004 ÖLFLEX TRAIN 350 300V 12X1 LAPP ÖLFLEX TRAIN 350 300V 12X1

Brand: LAPP | Manufacturer Part Number: 15350004



Manufacturer	LAPP
MPN / Reference	15350004
Catalog number	ÖLFLEX TRAIN 350 300V 12X1
Category	Power cable less 1 kV, for permanent installation
Minimum order	1 m.
Document ID	EO-5524ABEDB2
Generated	2026-08-03

Product Overview

ÖLFLEX TRAIN 350 300V 12X1

ÖLFLEX® TRAIN 350 300V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ÖLFLEX TRAIN

Additional Product Information

ÖLFLEX® TRAIN 350 300V - Control cable EN 50264-3-2 MM, 300/500V for high requirements in railways/rolling stock; EN

45545: HL1-HL3, NF F 16-101: C/F0

Meets EN 50264-3-2 type MM and

EN 45545-2

High temperature resistance: -50°C up to 120°C

Highly oil- and fuel-resistant

Benefits

Good chemical resistance please see Appendix T1

Resistant to mechanical influences in harsh environmental conditions

Extended temperature range

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

Application range

For use in railway vehicles and buses, for fixed installations and applications where limited movement may occur

Suitable for connecting lamps, heating equipment, switchgear, terminal boxes and power supply

For use in railway vehicles, for fixed installations and applications where limited movement may occur

Product features

Fire behaviour according to EN/IEC:

- Halogen-free acc. to EN 60754-1
- No corrosive gases acc. to EN 60754-2
- No fluorine acc. to EN 60684-2
- No toxic gases acc. to EN 50305
- Low smoke density acc. to EN 61034-2
- Flame-retardant acc. to EN 60332-1-2
- No flame propagation acc. to EN 60332-3-24 / EN 60332-3-25 /

EN 50305

Fire behaviour according to NF:

- Toxicity of gases acc. to NF X 70-100
- Low smoke density acc. to NF X 10-702
- No flame propagation acc. to NF C 32-070,

Cat. C1 and C2

Chemical properties:

- Oil resistant acc. to EN 50264-3-2
- Fuel resistant acc. to EN 50264-3-2
- Acid resistant acc. to....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 15350004 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.