

## INDUSTRIAL COMPONENT DATA

**15361006 ÖLFLEX TRAIN 361 1,8kV 1X25 BK LAPP ÖLFLEX TRAIN 361 1,8kV 1X25 BK**

Brand: LAPP | Manufacturer Part Number: 15361006



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | LAPP                                            |
| MPN / Reference | 15361006                                        |
| Catalog number  | ÖLFLEX TRAIN 361 1,8kV 1X25 BK                  |
| Category        | Power cable >= 1 kV, for permanent installation |
| Minimum order   | 1 m.                                            |
| Document ID     | EO-F3791E49B4                                   |
| Generated       | 2026-08-04                                      |

**Product Overview**

ÖLFLEX TRAIN 361 1,8kV 1X25 BK

ÖLFLEX® TRAIN 361 1,8kV

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path LAPP &gt; ÖLFLEX TRAIN

**Additional Product Information**

ÖLFLEX® TRAIN 361 1,8kV - Single-core EN 50264-3-1 type M, 1,8/3kV for high requirements in railways/rolling stock; EN

45545: HL1-HL3, NF F 16-101: C/F1

Meets EN 50264-3-1 type M and

EN 45545-2

High temperature resistance: -50°C up to 120°C

Highly oil- and fuel-resistant

Benefits

Good chemical resistance please see Appendix T1

Resistant to mechanical influences in harsh environmental conditions

Extended temperature range

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

Application range

For use in railway vehicles, for fixed installations and applications where limited movement may occur

Suitable for connecting lamps, heating equipment, switchgear, terminal boxes and power supply

Also applicable within oily environments and areas with increased ambient temperature

#### Product features

Fire behaviour according to EN/IEC:

- Halogen-free acc. to EN 60754-1
- No corrosive gases acc. to EN 60754-2
- No fluorine acc. to EN 60684-2
- No toxic gases acc. to EN 50305
- Low smoke density acc. to EN 61034-2
- Flame-retardant acc. to EN 60332-1-2
- No flame propagation acc. to

EN 60332-3-24 / EN 60332-3-25 /

EN 50305

Fire behaviour according to NF:

- Toxicity of gases acc. to NF X 70-100
- Low smoke density acc. to NF X 10-702
- No flame propagation acc. to NF C 32-070,

Cat. C1 and C2

Chemical properties:

- Oil resistant acc. to EN 50264-3-1
- Fuel resistant acc. to EN 50264-3-1
- Acid resistant acc. to EN 50264-3-1
- Alkali resi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 15361006 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.