

**INDUSTRIAL COMPONENT DATA**

# 19114000 EPIC H-B 24 TSB M25 ZW. HOOD LAPP EPIC H-B 24 TSB M25 ZW. HOOD

Brand: LAPP | Manufacturer Part Number: 19114000



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 19114000                           |
| Catalog number  | EPIC H-B 24 TSB M25 ZW. HOOD       |
| Category        | Housing for rectangular connectors |
| Minimum order   | 5 Pcs                              |
| Document ID     | EO-C1E3761EDE                      |
| Generated       | 2026-08-05                         |

## Product Overview

EPIC H-B 24 TSB M25 ZW. HOOD

EPIC® H-B 24 TSB

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; EPIC rectangular

## Additional Product Information

The robust metal housing with 2 double levers, a side cable entry and a neck is suitable for use in investment construction.

Non-slip ridges for comfortable disconnecting

For connection with counterpart with integrated cover

Protection rating UL50E tested

Benefits

Ideal for many applications due to a wide range of housings and inserts

Double lever version with 2 levers for increased safety

Application range

Plant engineering

Light &amp; sound technology

Plastics industry

Product features

Hood, low version

Dual levers

Side cable entry

Versions with neck

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating

IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 19114000 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.