

**INDUSTRIAL COMPONENT DATA**

# 19426500 H-A 3 MTGV M20 KPL. HOOD LAPP H-A 3 MTGV M20 KPL. HOOD

Brand: LAPP | Manufacturer Part Number: 19426500



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 19426500                           |
| Catalog number  | H-A 3 MTGV M20 KPL. HOOD           |
| Category        | Housing for rectangular connectors |
| Minimum order   | 10 Pcs                             |
| Document ID     | EO-8C718B3271                      |
| Generated       | 2026-08-06                         |

## Product Overview

H-A 3 MTGV M20 KPL. HOOD

EPIC® H-A 3 MTG

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

## Additional Product Information

The compact, robust metal housing is ideal for use with a rectangular connector and for supplying power in restricted spaces.

Small, rugged metal housing

Protection rating UL50E tested

Benefits

Housing in plastic or metal version for safe connections in the smallest possible space

Application range

Machine and equipment manufacturing

Control engineering

Electronic laboratory

Product features

Hood

Bolts for single lever

Straight cable entry

Versions with / without cable gland

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: powder-coated zinc die-casting, grey

Lever: zinc-plated steel

Protection rating

IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 19426500 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.