

INDUSTRIAL COMPONENT DATA

21700505 ED-PB-AX LAPP ED-PB-AX

Brand: LAPP | Manufacturer Part Number: 21700505



Manufacturer	LAPP
MPN / Reference	21700505
Catalog number	ED-PB-AX
Category	D-Sub connector
Minimum order	1 Pcs
Document ID	EO-80CBF01305
Generated	2026-08-02

Product Overview

ED-PB-AX

EPIC® DATA PB Sub-D

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > EPIC DATA Copper

Additional Product Information

PROFIBUS Sub-D connector, screw terminals, integrated bus termination, optional LED diagnostic/interfaces, cable outlet 35°/90°/180°

Optional with LED diagnostic

M12 and REPEATER version

Versions with 2nd Sub-D interface

Benefits

Easy connection with tried-and-tested M12 / screw terminal technology

sensor/ ac

Terminating resistor (integrated) can be switched

REPEATER version: Regeneration of data signal

(slope, power and mark-to-space ratio)

ATEX version: For use within intrinsically-safe circuits in zone 2 areas with an explosion hazard (explosive gas atmosphere occurs only rarely and briefly)

Product features

Max. transmission rate 12 Mbit/s possible

Current consumption max. 12,5 mA

(with LED 35 mA / REPEATER 100 mA)

Supply voltage 4.75 - 5.25 V DC

(supplied from the terminal)

Terminating resistor "ON" - the outbound bus cable is disconnected

REPEATER version: Easy extension of the PROFIBUS network:

- up to 3 repeaters
- 1 additional PROFIBUS segment
- galvanic isolation

Norm references / Approvals

IEC 61158, IEC 61784

UL File No. E331560

ATEX version: DIN EN 60079-0:2006, DIN 60079-15:2005 (category 3G zone 2)

Product Make-up

D-Sub plug, 9-pin, fixing screws 4-40 UNC

Improved electromagnetic compatibility (EMC) by metallized housing

Versions with additional Sub-D interface for programming/diagnostic ("PG")

For cable outer diameter: 5 - 8 mm / M12 B-coded cordsets

LED Version indicate:

bus operation - (green)

station transmission - (blue)

terminating resistor "on" - (orange)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 21700505 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.