

INDUSTRIAL COMPONENT DATA

2170143 UNITRONIC LAN 500 S/FTP Cat.6A LAPP UNITRONIC LAN 500 S/FTP Cat.6A

Brand: LAPP | Manufacturer Part Number: 2170143

LAPP KABEL STUFGART UNITRONIC® LAN 500 S/FTP Cat.6A (42x2xAWG22/1)

Manufacturer	LAPP
MPN / Reference	2170143
Catalog number	UNITRONIC LAN 500 S/FTP Cat.6A
Category	Data and communication cable
Minimum order	100 m.
Document ID	EO-B5EB6BDBD7
Generated	2026-08-05

Product Overview

UNITRONIC LAN 500 S/FTP Cat.6A

UNITRONIC® LAN 500 Cat.6

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > UNITRONIC LAN cabling

Additional Product Information

The LAN cable with a characteristic impedance of approximately 100 ohms is suitable for structured building wiring networks. It has solid core conductor and high-quality shielding.

CPR: Article number choice under www.lappkabel.com/cpr

Benefits

LAN cables for structured building cabling according to EN 50173 and ISO/IEC 11801

Application range

Mainly used where the terminal density is very high, e.g. for wiring office, administration and development buildings in the tertiary area (floor wiring).

Cable length in tertiary area (horizontal area, floor) should not exceed a length of 100 m in accordance with the ISO/IEC 11801 and EN 50173 standards (90 m in cable duct + 10 m in working area)

Product features

Transfer of digital and analogue data signals

Flame retardant acc. to IEC 60332-1-2

2170195

2170196: flame retardant acc. to IEC 60332-1-2 and IEC 60332-3-24

IEEE 802.3: 10/100/1000Base-T, 10GBase-T IEEE 802.5: ISDN; FDDI; ATM

Norm references / Approvals

Class EA out of the standard ISO/IEC 11801 corresponds to Cat.6A

LAN Cat.6A cables from Lapp Kabel for "Structured Cabling Systems" meet the requirements in accordance with EIA/TIA-568 and TSB36, as well as ISO/IEC 11801 or EN 50173 (Class EA - permanent link).

Product Make-up

Solid conductor

U/FTP: aluminium compound foil as pair screening

F/FTP: aluminium compound foil as overall screening and pair screening

S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
outer sheath either as PVC (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 2170143 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.